

S835

DIGITAL ELECTRONIC 3-D WHEEL BALANCER

WITH VIDEO DISPLAY, LASER LINE AND LED LIGHT

3-D

Digital 3-D electronic measuring

10"-30"

Rim diameter range

75 KG

Max wheel weight

5.3 s

Fast 5.3-second cycle time

19" TFT

HD colour video display

CE

CE certified

GIULIANO

Supplied & Supported by

HDL Auto Equip

Installation, training &
genuine warranty included



STANDARD FEATURES

DONNEES TECHNIQUES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10" – 30" / 255–765 mm
Rim width	1.5" – 20" / 40–510 mm
Power supply	230V 1ph (50/60) Hz
Cycle time	5.3 s (5 3/4"×14") 15 kg
Balancing speed	< 150 rpm
Balancing precision	± 1 g
Net weight (with guard)	102 kg

Specifications subject to change. Contact HDL Auto Equip for details.

FUNCTIONS & FEATURES

CARACTÉRISTIQUES

› Flat screen HD colour video monitor 19" TFT	› NWN System
› Automatic measuring of wheel diameter & distance	› Special ALU-S program
› Automatic START and STOP	› FES function
› Pedal brake	› OPTIMATCH function
› Static and dynamic balancing	› Self-diagnosis & self-calibration
› Huge combination of ALU programs	› Optimisation of static unbalance
› OPF function	› Complete with cones & quick clamping ring nut
› Laser line — exact positioning of adhesive weights	› LED light on working area
› CLIP system for application of stick-on weight	› SONAR auto wheel width measurement (standard)
› Complete with wheel guard	

DIMENSIONS

mm

Overall width	1,150 mm
Overall depth	1,350 mm
Overall height (with guard)	1,540 mm
Overall height (working)	1,280 mm
Net weight (with guard)	102 kg

STANDARD ACCESSORIES

ACCESSOIRES STANDARD

› Balancing cone set
› Quick clamping ring nut
› Wheel guard
› Calibration weight
› Wing nut spanner