

GIULIANO



S226

Pro

AUTOMATIC TILT BACK TYRE CHANGER

WITH DUAL ASSIST ARM

- AUTO** Automatic operation
- 10"-24"** Rim clamping range
- HPF** Dual assist arm — standard
- CAR** Passenger car tyres
- CE** CE certified

Supplied & Supported by

HDL Auto Equip

Installation, training &

genuine warranty included

STANDARD FEATURES

DONNEES TECHNIQUES

Rim clamping from outside	10" – 24" *
Max. tyre diameter	1100 mm (43")
Max. tyre width	380 mm (15")
Bead breaker cylinder force at 10 Bar	30,800 N
Air pressure (service)	8 Bar (116 Psi)
Motor power	0.55 kW (240V)
Rotation speed	7 rpm
Working air pressure	3.5 Bar (50 Psi)

* Adjustable — optional configurations available on request. Contact HDL Auto Equip for details.

FUNCTIONS & FEATURES


CARACTÉRISTIQUES

› Tilting head for standard & low-profile tyre applications	› HPF dual assist arm — included as standard
› Bead breaker double-effect cylinder Ø 200 mm	› Tubeless tyre bead-seating system (optional)
› Clamping range 10"–24" with reinforced chassis	› Ideal for general mechanics & new tyre store start-ups
› Platform contour with 12 mm wall thickness	› Suitable for all standard passenger car tyre service
› Tyre inflation by pedal (optional)	› CE certified

DIMENSIONS

mm

Overall length (with arm)	~1190 mm
Overall height (column up)	~1800 mm
Net weight	Contact HDL Auto Equip



STANDARD ACCESSORIES

ACCESSOIRES STANDARD

